


HAVING 3 CORE CABLE ASSY WITH 3/4" CONDUIT FITTING (SEE NOTE-04)



WIRING DIAGRAM

AT RAPID PRESSURE RISE,

11 OPENS ON 12 AND CLOSES ON 14

SWITCH RATING

15 AMP @ 125, 250, 480 VAC
 0.5 AMP @ 125 VDC
 25 AMP @ 250 VDC] NON-INDUCTIVE

STYLE LIST

STYLE NO.	ITEM INCLUDED	DESCRIPTIONS
BL 9046056015	COMPLETE ASSY (INCLUDING 3-CORE CABLE ASSY WITH 3/4" CONDUIT FITTINGS)	RAPID PRESSURE RISE RELAY CABLE LENGTH=13 METERS.

NOTES:-

- 01.
02. FOR OIL SPACE INSTALLATION ONLY.
03. UNIT MUST BE MOUNTED HORIZONTALLY WITH VENT UP AS SHOWN
04. LENGTH X=13 METERS FOR STYLE NO. BL-9046056015 SEPARATE INDENT TO BE RAISED FOR HIGHER LENGTH OF CABLE BY DEFINING X- VALUE.

ADDITIONAL INFORMATION STANDARD				TYPE OF PRODUCT OR		TRANSFORMER/REACTOR								
STATUS OF DRAWING				NAME OF CUSTOMER/PROJECT										
DISTRIBUTION OF PRINTS				BHRAT HEAVY ELECTRICALS LTD.		DRN	NAME	SIGN	DATE	NO. OF VAR				
TRE	TRM	TRX	BHPAL		CHD		Sd/-	10.11.85						
1	3	1			APPD		Sd/-							
REV 04	DATE 04/05/13	ALT CAD	INTEN TP	REV 03	DATE 21-3-05	ALTERED HALDER	CHECKED N.G.PANICKER	APPROVED S.G.BHAKADE	DEPT TRE CODE 406	SCALE NTS	WEIGHT(kg) 5	REF TO ASSY DRG	ITEM NO.	NO. OF ITEM
NOTE 01 DELETED.				STYLE LIST INCLUDED. NOTE-04 ADDED FOR CALLING EXTRA LENGTH. IMPORTANT NOTE DELETED.				TITLE		Rapid Pressure Rise Relay(Oil.)		CARD CODE	DRAWING NO. 3 499 00 00023	REV 04

IT MUST NOT BE USED DIRECTLY OR INDIRECTLY IN ANY WAY DETRIMENTAL TO THE INTERESTS OF THE COMPANY.