

Control Relays	:	a) Line drop compensator with resistive & reactive compensation either polarity up to 20% and suitable for operation with 1A,5VA CT.
	:	b) One pair of normally open potential free contact of rating 5A/230V AC resistive load / inductive load for each "Raise" & "Lower" control relays.
	:	c) One pair of normally potential free OPEN contacts of rating 5A/220V DC resistive load for "PT supply fail/under voltage" alarm.
Control Operations	:	Single pulse operation with Approx. 2Sec.on time.
Operation Temperature	:	0 to 45 deg C.
Over All Dimension	:	372mm(H)* 145mm(W)*260mm(D)
Panel cut-out Dimensions	:	330mm(H)*135mm(W)

Notes:-

1. Two copies of each Descriptive leaflets, Dimension Drawings with mounting Arrangements & connection Diagram shall be furnished with offer.
2. Four copies of Instruction manual & test certificates shall be furnished before Dispatch of equipment.

Notes:-

1. Two copies of each Descriptive leaflets, Dimension Drawings with mounting arrangements & connection Diagram shall be furnished with offer.
2. Four copies of Descriptive leaflets, Dimension Drawings with mounting arrangements, Connection Diagram, Instruction manual & type test certificates shall be furnished before dispatch of equipment.

बिना उदर
25/07/2013