



	INSULATION SKETCH	IN. SK. 46089
	INSULATION SYSTEMS ENGINEERING	Rev. No.: 00
	<b>SEMI-CONDUCTING TAPE</b>	Rev. Dt.: 30/07/2016
		Sht. 2 of 2 shts.
<p><b>5.5 Composition :</b></p> <p>Woven polyester fabric tape impregnated with silicone carbide filled varnish in B-stage.</p> <p><b>6.0 SHELF LIFE :</b></p> <p>Minimum 1 year at <math>\leq 5^{\circ}\text{C}</math> / Minimum 6 months at <math>&gt; 5^{\circ}\text{C}</math> to <math>\leq 25^{\circ}\text{C}</math>.</p> <p><b>7.0 PACKING :</b></p> <p>6.1 Tape shall be supplied in rolls, with roll length of 50 m.</p> <p>6.2 Tape rolls shall be suitably packed so that the material is protected from dirt, dust and moisture and is not damaged during transportation.</p> <p><b>8.0 MARKING ON ROLLS :</b></p> <p>7.1 Semi – Conducting tape (IN.SK. 46089)</p> <p>7.2 Supplier's name and grade of material</p> <p>7.3 Supplier's lot no. / batch no.</p> <p>7.4 Dimensions</p> <p>7.5 Purchase order no.</p> <p>7.6 Shelf life</p> <p><b>9.0 TEST CERTIFICATE :</b></p> <p>The supplier shall furnish 4 copies of test certificate as per specification.</p> <p><b>10.0 ACCEPTANCE CRITERIA :</b></p> <p>Material shall be accepted on the basis of test and / or compliance certificate furnished by the supplier and / or testing carried out at BHEL end.</p> <p><b>11.0 REJECTION :</b></p> <p>BHEL reserves the right to reject the entire lot of the material if found not conforming to stipulations of this specification. Parts of the lot not subjected to testing but found to be defective and those with hidden defect can be rejected later on, also. Material is also liable to be rejected if any problems related to application are observed in shop within the shelf life of material.</p> <p><b>11.0 CROSS REFERRED STANDARD :</b></p> <p>NIL.</p>		
ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE STATED		