

GATOS - 3300V range								
U _{DC} 1650 V			U _N 2600 V			U _S 3300 V		U _{max} 900 V _{rms}
C (μF)	I _{max} (A _{rms})	I _p (A)	R _s (mW)	L (nH)	R _θ (°C/W)	Dimensions (±2 mm)		Part Number
						Diameter ()	Height (H)	
0.25	35	700	1.40	6	12.00	45	48	GT1509A
0.5	25	800	1.75	8	9.80	45	62	GT1818
1.0	45	1500	0.90	8	6.70	60	62	GT1819
1.5	60	2300	0.60	7	5.43	70	62	GT1820
2.0	80	3100	0.45	7	4.50	80	62	GT1821
2.5	85	3900	0.35	6	3.81	90	62	GT1822
3.0	90	4600	0.30	5	3.51	95	62	GT1823
4.0	75	3400	0.60	7	3.31	85	86	GT1824
5.0	85	4200	0.50	6	2.85	95	86	GT1825

GATOS - 3600V range								
U _{DC} 2000 V			U _N 2900 V			U _S 3600 V		U _{max} 1100 V _{rms}
C (μF)	I _{max} (A _{rms})	I _p (A)	R _s (mW)	L (nH)	R _θ (°C/W)	Dimensions (±2 mm)		Part Number
						Diameter ()	Height (H)	
0.25	25	800	2.35	10	8.93	40	84	GT1826
0.5	30	1000	2.45	13	6.41	45	104	GT1827
1.0	50	2100	1.25	13	4.53	60	104	GT1828
1.5	65	3100	0.80	11	3.73	70	104	GT1829
2.0	75	4100	0.60	11	3.42	75	104	GT1830
2.5	90	5100	0.50	11	2.91	85	104	GT1831
3.0	90	6200	0.40	10	2.70	90	104	GT1832
4.0	90	8200	0.30	10	2.20	105	104	GT1833