



6 HOLES M10X12 DEEP  
USE FLAT DRILL  
(MUST NOT BREAK  
THRO.) EQUALLY  
SPACED ON 80 P.C.D.

DETAIL - 'A'  
(SCALE: 1:1)

FINISH: NATURAL

NOTE:—

1—THE OUTER SURFACE OF THE SPRING  
GUIDE PLATE SHOULD BE FREE FROM  
ANY SHARP EDGE, DENTS, CRACKS  
AND SHOULD HAVE A UNIFORM  
SMOOTH FINISH.

950140	001	150 DIA X 50 WROUGHT AL. ALLOY ROD.	GR-64430 (WP)		2-25 Kg.
VAR. NO.	ITEM NO.	DESCRIPTION	DRAWING NO.		UNIT WT.
64 86	76 78 79 25	58 59 60	57	AA12330	58
28	28	28	28	MATL. CODE	54
28	28	28	28	MATL. SPECN.	51 C
28	28	28	28	VAR.	33 48
28	28	28	28	UNIT	54
28	28	28	28	QTY.	71
28	28	28	28		66

ADDITIONAL INFORMATION

STATUS OF DRAWING

DISTRIBUTION OF PRINTS

BCE	BCM	TCX	QAX
1	4	1	1

REV. DATE  
ALTERED  
CHECKED

TYPE OF PRODUCT 36KV 1250A OIP WALL BUSHING  
OR  
NAME OF CUSTOMER / PROJECT



BHARAT HEAVY ELECTRICALS LTD  
BHOPAL

DEPT. CODE	GRADE OF UN TOL. DIM. C.M.F.	SCALE	WEIGHT (KG)	DRN.	B.R. MOHE	SIGN	DATE	NO. OF VAR.
421		1:2	1-32				30-4-90	73
				APPD.	R.K.A.		2-5-90	74
				REF. TO ASSY. DRG.				75
								NO. OF ITEMS
								808
								76
								77
								78
								79
								80
								81
								82
								83
								84
								85
								86
								87
								88
								89
								90
								91
								92
								93
								94
								95
								96
								97
								98
								99
								100

TITLE  
SPRING GUIDE PLATE

DRAWING NO.

35380401129

SHEET NO. 1

NO. OF SHEETS 1